

NX-3200/3300/3400 **NXDN™** **DMR** **Gen2** **Bluetooth®** **GPS** **FleetSync®**

MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

This versatile handheld radio supports both NXDN™ and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models with 14-pin Universal connector are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.

Features

- Multi-protocol digital radio: Designed to operate under NXDN or DMR digital, and FM analog protocols
- NXDN Conventional and Type-C & Gen2 Trunking
- DMR Tier 2 Conventional & Site Roaming
- DMR Auto Slot Select
- DMR Tier 3 Trunking
- Mixed Digital & FM Analog Operation allows gradual migration at your own pace
- 4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- 5-Line Text Message Frame (3 Lines of Text, icon & key guide)
- 7-color Light Bar Indicator on the top panel. Individual color can be set for each channel
- 4-way Directional-pad (D-pad) for intuitive control and operation
- Built-In GPS Receiver/Antenna for effective fleet and incident management
- Built-in Bluetooth® for hands-free operation for IoT applications - Applicable Bluetooth profiles: HSP (Headset Profile) and SPP (Serial Port Profile)
- Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP
- Optional DES and AES Encryption
- Built-in Motion Sensor (Man-down, Stationary and Motion Detection)
- IP54/55/67 and MIL-STD-810 C/D/E/F/G
- 1 Watt Audio Output Power
- UHF: 120 MHz capability
- Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)
- 512 CH/128 Zones (64 CH/4 Zones for Basic model)
- Maximum of 1,000 CH/Radio with option
- Intrinsically Safe Option
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check



Full Keypad Model Standard & Basic Models

7-color Light Bar Indicator

14-pin Universal Connector offers reliable connectivity even in harsh environment with a wide-range of accessories.

Digital – NXDN™ Mode

NXDN Conventional	Remote Monitor
NXDN Type-C & Gen2 Trunking	All Group Call
6.25 & 12.5 kHz Channels	Over-the-Air Alias (OAA)
Advanced GPS	Over-the-Air Programming (OTAP)

Digital – DMR Mode

Two-slot TDMA in 12.5 kHz channels	Call Interruption
DMR Tier 2 Conventional / Site Roaming	Dual-slot Direct Mode
DMR Auto Slot Select	Optional ARC4 Encryption
DMR Tier 3 Trunking	Energy Efficient

Analog – FM Mode

Conventional & LTR Trunking	MDC-1200: PTT ID ANI / Caller ID
FleetSync/II: PTT ID ANI / Caller ID Display,	Display, Emergency, Radio Check /Inhibit
Selective Group Call, Emergency Status	QT / DQT, DTMF, 2-Tone
Text Messages	Built-in Voice Inversion Scrambler



Multi-Protocol

Unsurpassed interoperability for Enterprise radio users with the freedom to migrate at your own pace.



Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.



Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

Accessories

All accessories may not be available in all markets. Contact an authorized KENWOOD dealer for details and complete list of all accessories.

KNB-55L/57L/78L

Li-ion Battery Pack (7.4V/1480mAh, 7.4V/2000mAh, 7.4V/2860mAh)



KNB-56N

Ni-MH Battery Pack (7.2 V/1400 mAh)



KNB-79LCM

Li-ion Battery Pack (7.4 V/2860 mAh, Intrinsically Safe)



KBP-5

Battery Case (6 AA)



KSC-25LSK/25SK

Rapid Charger (Li-ion Only/Tri-Chem)



KSC-256AK

Multiple Charger (6-pocket)



KMB-30A

Mounting Bracket (for KSC-256AK)



KVC-23

Vehicular Charger



KRA-22/23

VHF/UHF Low Profile Helical Antenna



KRA-25

High Gain Whip Antenna



KRA-26/ 27

VHF Helical Antenna UHF Whip Antenna



KRA-28

Broadband VHF Whip Antenna



KRA-41/42

VHF/UHF Stubby Antenna



KRA-24

800MHz Whip Antenna



KRA-32K

700/800MHz Whip Antenna



KRA-36

700/800MHz Stubby Antenna



KRA-38K

800/900MHz Whip Antenna (including NX-3400/NX-3420)



KRA-39

900MHz Stubby Antenna



KEP-1

3.5mm earphone kit for KMC-41/42W 54W/70M/72W Speaker Mics



KMC-70M

Speaker Microphone with Active Noise Reduction (IP54/55/67)



KMC-72W

Noise-cancelling Speaker Microphone (IP54/55/67)



KBH-11

Belt Clip (2.5")



KAS-20

AVL & Dispatch Software



KPG-180AP

OTAP Manager



KLH-206/207

Leather/Nylon Case



Specifications

General	NX-3200	NX-3300	NX-3400
Frequency Range	136-174 MHz	400-520 MHz	TX/RX: 851-870, 935-941 MHz TX:806-825, 896-902 MHz
Max. Channels Per Radio		Up to 1000 CH with option	
Number of Channels		512 (64 for no LCD models)	
Number of Zones		128 (4 for no LCD models)	
Channel Spacing			
Analog	12.5/15/25*/30* kHz	12.5/25* kHz	12.5/25* kHz
Digital	6.25 kHz/12.5 kHz	6.25 kHz/12.5 kHz	6.25 kHz/12.5 kHz
Power Supply		75V DC ± 20%	
Battery Life 5-5-90	(FDMA conventional / Trunking, TDMA Conventional / Trunking)		
KNB-55L (1,480 mAh)	8.5 / 6.5 hours, 12.5 / 9 hours		9 / 7 hours, 12 / 9 hours
KNB-56N (1,400 mAh)	7.5 / 6 hours, 11 / 8 hours		8 / 6 hours, 10.5 / 8 hours
KNB-57L (2,000 mAh)	12 / 9.5 hours, 17.5 / 13 hours		13 / 10 hours, 17 / 13 hours
KNB-78L (2,860 mAh)	17.5 / 13.5 hours, 25 / 18.5 hours		18.5 / 14 hours, 24 / 18.5 hours
KNB-79LCM (2,860 mAh)	15 / 11.5 hours, 21.5 / 16 hours		15.5 / 12 hours, 20.5 / 16 hours
Operating Temperature		-22°F to +140°F (-30°C to +60°C)	
Frequency Stability		±0.5 ppm (-30°C to +60°C; +25°C Ref.)	
Dimensions		(W x H x D) Projections Not Included	
Radio Only		2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-55L (1,480 mAh)		2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-56N (1,400 mAh)		2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)	
KNB-57L (2,000 mAh)		2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)	
KNB-78L, KNB-79LCM		2.20 x 4.71 x 1.77 in (56 x 119.6 x 44.9 mm)	
Weight Radio Only		7.8 oz (220 g)	
KNB-55L (1,480 mAh)		11.1 oz (315 g)	
KNB-56N (1,400 mAh)		14.5 oz (410 g)	
KNB-57L (2,000 mAh)		12.0 oz (340 g)	
KNB-78L, KNB-79LCM		13.6 oz (385 g) / 13.9 oz (395 g)	
FCC ID	K44479000	K44479100	K44502500
IC Certification	282F-479000	282F-479100	282F-502500

*25 and 30 kHz in VHF/UHF Bands (except T-Band) are not included in the models sold in the USA or US territories.
**800MHz band only
Analog measurements made per TIA603. Specifications are measured according to applicable standards.
Battery Life is measured by Battery Save ON, GPS/Bluetooth OFF, 4 W for VHF/UHF and 3 W for 800/900MHz Bands
Specifications are subject change without notice, due to advancements in technology.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	5001/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	5011/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	5021/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	5031/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	5051/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	5061/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	5071/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	5091/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	5101/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, II, V	516.5/Procedure I, IV	516.6/Procedure I, IV

International Protection Standard

Dust & Water Protection* IP54/55/67

* Audio accessory or cover must be installed.

JVCKENWOOD USA Corporation

Communications Sector Headquarters
1440 Corporate Drive | Irving, TX 75038

Order Administration/Distribution
4001 Worsham Ave. | Long Beach, CA 90808

www.kenwood.com/usa

JVCKENWOOD Canada Inc.

Canadian Headquarters and Distribution
6685 Millcreek Drive, Unit 8, Mississauga, ON L5N 5M5

www.kenwood.com/ca



ISO9001 Registered
Communications Systems Business Unit
JVCKENWOOD Corporation

ADS#21122 Print in USA